
XW VA
Fitting, angle 90°

Properties

Connection 1 + 2	metric cylindrical outer thread
Sealing form 1 + 2	24° inner cone
Design	Fitting
Construction	Angle 90°
Standard	DIN 3905
Scope of supply	Socket (without union nut and cutting ring)
Material	Stainless steel





Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item

Identification	Series	Operating pressure	External pipe Ø (mm)	L2 (mm)	L7 (mm)	AF (mm)
XW 04 LL VA	LL	PN 100	4	11,0	15	9
XW 06 LL VA	LL	PN 100	6	9,5	15	9
XW 08 LL VA	LL	PN 100	8	11,5	17	12
XW NW 04 HL VA	L	PN 315	6	12,0	19	12
XW NW 06 HL VA	L	PN 315	8	14,0	21	12
XW NW 08 HL VA	L	PN 315	10	15,0	22	14
XW NW 10 HL VA	L	PN 315	12	17,0	24	17
XW NW 13 HL VA	L	PN 315	15	21,0	28	19
XW NW 16 HL VA	L	PN 315	18	23,5	31	24
XW NW 20 HL VA	L	PN 160	22	27,5	35	27
XW NW 25 HL VA	L	PN 160	28	30,5	38	36
XW NW 32 HL VA	L	PN 160	35	34,5	45	41
XW NW 40 HL VA	L	PN 160	42	40,0	51	50
XW NW 03 HS VA	S	PN 630	6	16,0	23	12
XW NW 04 HS VA	S	PN 630	8	17,0	24	14
XW NW 06 HS VA	S	PN 630	10	17,5	25	17
XW NW 08 HS VA	S	PN 630	12	21,5	29	17
XW NW 10 HS VA	S	PN 630	14	22,0	30	19
XW NW 13 HS VA	S	PN 400	16	24,5	33	24
XW NW 16 HS VA	S	PN 400	20	26,5	37	27
XW NW 20 HS VA	S	PN 400	25	30,0	42	36
XW NW 25 HS VA	S	PN 400	30	35,5	49	41
XW NW 32 HS VA	S	PN 315	38	41,0	57	50

Series: LL = Very light L = Light S = Heavy – PN = Nominal pressure PB = Max. operating pressure – Ø = External pipe diameter

Product versions

XW	Fitting, angle 90°, Steel
W VA W90	Fitting, angle 90°, Stainless steel

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.