
XWM VA
Screw-in fitting, angle 90°

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	Shape B
Connection 2	metric cylindrical outer thread
Sealing form 2	24° inner cone
Design	Screw-in fitting
Construction	Angle 90°
Standard	DIN 2353 ISO 8434-1
Scope of supply	Socket (without union nut and cutting ring)
Material	Stainless steel





Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item

Identification	Series	Operating pressure	Ø d2 (mm)	G	D (mm)	i (mm)	L4 (mm)	L5 (mm)	L7 (mm)	AF (mm)
XWM NW 20 HL VA	L	PN 160	22	M 26 x 1.5	31	16	27,5	26	35	27
XWM NW 25 HL VA	L	PN 160	28	M 33 x 2	39	18	30,5	30	38	36
XWM NW 32 HL VA	L	PN 160	35	M 42 x 2	49	20	34,5	34	45	41
XWM NW 40 HL VA	L	PN 160	42	M 48 x 2	55	22	40,0	39	51	50
XWM NW 16 HS VA	S	PN 400	20	M 27 x 2	32	16	26,5	26	37	27
XWM NW 20 HS VA	S	PN 250	25	M 33 x 2	39	18	30,0	30	42	36
XWM NW 25 HS VA	S	PN 160	30	M 42 x 2	49	20	35,5	34	49	41
XWM NW 32 HS VA	S	PN 160	38	M 48 x 2	55	22	41,0	39	57	50

Series: LL = Very light L = Light S = Heavy – PN = Nominal pressure PB = Max. operating pressure – Ø d2 = External pipe diameter

Product versions

XWM	Screw-in fitting, angle 90°, Steel
WM VA	Screw-in fitting, angle 90°, Stainless steel

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.