


Properties

Connection 1	BSPT conical external threads
Sealing form 1	thread seal
Connection 2	metric cylindrical outer thread
Sealing form 2	24° inner cone
Design	Screw-in fitting
Construction	Angle 90°
Standard	DIN 2353 ISO 8434-1
Scope of supply	Socket (without union nut and cutting ring)
Material	Steel
Surface	electro galvanised



Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

Item

Identification	Series	Operating pressure	Ø d2 (mm)	G	i (mm)	L4 (mm)	L5 (mm)	L7 (mm)	AF (mm)
XWR 04 LL	LL	PN 100	4	R 1/8" K	8	11,0	17,0	15,0	9
XWR 05 LL	LL	PN 100	5	R 1/8" K	8	8,0	17,0	13,5	9
XWR 06 LL	LL	PN 100	6	R 1/8" K	8	9,5	17,0	15,0	9
XWR 08 LL	LL	PN 100	8	R 1/8" K	8	11,5	20,0	17,0	12
XWR 10 LL	LL	PN 100	10	R 1/4" K	12	15,5	26,0	21,0	14
XWR 12 LL	LL	PN 100	12	R 1/4" K	12	12,0	21,5	18,0	17
XWR NW 04 HL	L	PN 315	6	R 1/8" K	8	12,0	20,0	19,0	12
XWR NW 04 HL 1/4	L	PN 315	6	R 1/4" K	12	14,0	26,0	21,0	12
XWR NW 04 HL 3/8	L	PN 315	6	R 3/8" K	12	17,0	28,0	24,0	17
XWR NW 06 HL	L	PN 315	8	R 1/4" K	12	14,0	26,0	21,0	12
XWR NW 06 HL 1/8	L	PN 315	8	R 1/8" K	8	14,0	26,0	21,0	12
XWR NW 06 HL 3/8	L	PN 315	8	R 3/8" K	12	19,0	28,0	26,0	17
XWR NW 06 HL 1/2	L	PN 315	8	R 1/2" K	13	20,0	34,0	27,0	19
XWR NW 08 HL	L	PN 315	10	R 1/4" K	12	15,0	27,0	22,0	14
XWR NW 08 HL 1/8	L	PN 315	10	R 1/8" K	8	15,0	27,0	22,0	14
XWR NW 08 HL 3/8	L	PN 315	10	R 3/8" K	12	17,0	28,0	24,0	17
XWR NW 08 HL 1/2	L	PN 316	10	R 1/2" K	14	23,0	34,0	30,0	19
XWR NW 10 HL	L	PN 315	12	R 3/8" K	12	17,0	28,0	24,0	17
XWR NW 10 HL 1/4	L	PN 315	12	R 1/4" K	12	17,0	28,0	24,0	17
XWR NW 10 HL 1/2	L	PN 315	12	R 1/2" K	14	23,0	34,0	30,0	19
XWR NW 10 HL 3/4	L	PN 315	12	R 3/4" K	16	28,0	42,0	35,0	27
XWR NW 13 HL	L	PN 315	15	R 1/2" K	14	21,0	34,0	28,0	19
XWR NW 13 HL 1/4	L	PN 315	15	R 1/4" K	12	21,0	34,0	28,0	19
XWR NW 13 HL 3/8	L	PN 315	15	R 3/8" K	12	21,0	34,0	28,0	19
XWR NW 16 HL	L	PN 315	18	R 1/2" K	14	23,5	36,0	31,0	24
XWR NW 16 HL 3/8	L	PN 315	18	R 3/8" K	12	23,5	36,0	31,0	24
XWR NW 16 HL 3/4	L	PN 315	18	R 3/4" K	16	27,5	42,0	35,0	27
XWRK NW 20 HL	L	PN 160	22	R 3/4" K	16	27,5	42,0	35,0	27
XWR NW 03 HS	S	PN 400	6	R 1/4" K	12	16,0	26,0	23,0	12
XWR NW 04 HS	S	PN 400	8	R 1/4" K	12	17,0	27,0	24,0	14
XWR NW 06 HS	S	PN 400	10	R 3/8" K	12	17,5	28,0	25,0	17
XWR NW 08 HS	S	PN 400	12	R 3/8" K	12	21,5	28,0	29,0	17
XWR NW 08 HS 1/2	S	PN 400	12	R 1/2" K	14	23,5	34,0	31,0	19
XWR NW 10 HS	S	PN 400	14	R 1/2" K	14	22,0	32,0	30,0	19
XWR NW 13 HS	S	PN 400	16	R 1/2" K	14	24,5	32,0	33,0	24
XWR NW 16 HS 1/2	S	PN 400	20	R 1/2" K	14	26,5	42,0	37,0	27
XWR NW 13 HS 3/8	S	PN 400	16	R 3/8" K	12	24,5	32,0	33,0	24

Series: LL = Very light L = Light S = Heavy – PN = Nominal pressure PB = Max. operating pressure – Ø d2 = External pipe diameter



XWRK

Screw-in fitting, angle 90°



Product versions

XWRK VA	Screw-in fitting, angle 90°, Stainless steel
---------	--

WRK	Screw-in fitting, angle 90°, Steel
-----	------------------------------------