# G AB IR


Screw-on connector

HANSA-FLEX

## Properties

| | |
|---|---|
| **Connection 1** | BSP nut thread |
| **Sealing form 1** | 60° outer cone |
| **Connection 2** | BSP cylindrical internal threads |
| **Sealing form 2** | Flat seal |
| **Design** | Screw-on connector |
| **Construction** | straight |
| **Material** | Steel |
| **Surface** | electro galvanised |






## Item

| Identification | G1 + G2 | AF (mm) | S1 |
|---|---|---|---|
| **G AB 02 IR** | G 1/8" -28 | 14 | 14 |
| **G AB 04 IR** | G 1/4" -19 | 17 | 19 |
| **G AB 06 IR** | G 3/8" -19 | 22 | 22 |
| **G AB 08 IR** | G 1/2" -14 | 27 | 27 |
| **G AB 12 IR** | G 3/4" -14 | 32 | 32 |
| **G AB 16 IR** | G 1" -11 | 43 | 41 |
| **G AB 20 IR** | G 1.1/4" -11 | 50 | 50 |
| **G AB 24 IR** | G 1.1/2" -11 | 60 | 60 |

SW, S1, S2 = With across flats

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*