

G AJF HJOF VA

Connectors

Properties

Connection 1	ORFS nut threads
Sealing form 1	flat sealing
Connection 2	ORFS external threads
Sealing form 2	flat seal with O-ring
Design	Connectors
Construction	straight
Material	Stainless steel



Ordering information

Seals of NBR
FPM (Viton) on request

Item	G1	G2	AF (mm)	S1	OR
G AJF 04 HJOF 06 VA	9/16"-18 UNF	11/16" -16 UN	19	18	9.25 x 1.78
G AJF 06 HJOF 04 VA	11/16" -16 UN	9/16"-18 UNF	-	21	7.65 x 1.78
G AJF 08 HJOF 06 VA	13/16" -16 UN	11/16" -16 UN	22	24	9.25 x 1.78
G AJF 10 HJOF 08 VA	1" -14 UNS	13/16" -16 UN	22	30	12.42 x 1.78
G AJF 12 HJOF 06 VA	1.3/16" -12 UN	11/16" -16 UN	19	36	9.25 x 1.78
G AJF 12 HJOF 08 VA	1.3/16" -12 UN	13/16" -16 UN	32	36	12.42 x 1.78
G AJF 16 HJOF 08 VA	1.7/16" -12 UN	13/16" -16 UN	22	41	12.42 x 1.78
G AJF 16 HJOF 12 VA	1.7/16" -12 UN	1.3/16" -12 UN	41	41	18.77 x 1.78
G AJF 24 HJOF 16 VA	2" -12 UN	1.7/16" -12 UN	38	60	23.52 x 1.78

SW, S1, S2 = With across flats

Product versions

G AJF HJOF Connectors, Steel