


Properties			
Connection 1	NPT nut thread (NPSM)		
Sealing form 1	60° outer cone		
Connection 2	NPT external threads		
Sealing form 2	thread seal		
Design	Screw-in sockets		
Construction	straight		
Material	Steel		
Surface	electro galvanised		





Item					
Identification	G1	G2	AF	S1	
			(mm)		
G AN 02 HN	1/8" -27 NPT	1/8" -27 NPT	14	14	
G AN 04 HN	1/4" -18 NPT	1/4" -18 NPT	18	18	
G AN 04 HN 02	1/4" -18 NPT	1/8" -27 NPT	16	18	
G AN 04 HN 06	1/4" -18 NPT	3/8" -18 NPT	18	18	
G AN 06 HN	3/8" -18 NPT	3/8" -18 NPT	22	22	
G AN 06 HN 04	3/8" -18 NPT	1/4" -18 NPT	21	22	
3 AN 06 HN 08	3/8" -18 NPT	1/2" -14 NPT	22	22	
3 AN 08 HN	1/2" -14 NPT	1/2" -14 NPT	25	25	
3 AN 08 HN 04	1/2" -14 NPT	1/4" -18 NPT	24	25	
3 AN 08 HN 06	1/2" -14 NPT	3/8" -18 NPT	24	25	
3 AN 08 HN 12	1/2" -14 NPT	3/4" -14 NPT	29	25	
3 AN 12 HN	3/4" -14 NPT	3/4" -14 NPT	32	32	
3 AN 12 HN 08	3/4" -14 NPT	1/2" -14 NPT	32	32	
3 AN 12 HN 16	3/4" -14 NPT	1" -11.5 NPT	35	38	
3 AN 16 HN	1" -11.5 NPT	1" -11.5 NPT	38	38	
3 AN 16 HN 12	1" -11.5 NPT	3/4" -14 NPT	38	38	
3 AN 20 HN	1.1/4" -11.5 NPT	1.1/4" -11.5 NPT	48	48	
AN 24 HN 16	1.1/2" -11.5 NPT	1" -11.5 NPT	45	54	
3 AN 24 HN	1.1/2" -11.5 NPT	1.1/2" -11.5 NPT	54	54	
3 AN 32 HN	2" -11.5 NPT	2" -11.5 NPT	67	67	

SW, S1, S2 = With across flats