


# G HB HJL

## Screw-in sockets

### Properties

<b>Connection 1</b>	BSP external thread, cylindrical
<b>Sealing form 1</b>	60° inner cone
<b>Connection 2</b>	metric cylindrical outer thread
<b>Sealing form 2</b>	60° outer cone
<b>Design</b>	Screw-in sockets
<b>Construction</b>	straight
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



### Item

Identification	G1	G2	AF (mm)
<b>G HB 04 NW 06 HJL</b>	G 1/4" -19	M 14 x 1.5	19
<b>G HB 06 NW 10 HJL</b>	G 3/8" -19	M 18 x 1.5	22
<b>G HB 06 NW 13 HJL</b>	G 3/8" -19	M 22 x 1.5	22
<b>G HB 08 NW 08 HJL 20</b>	G 1/2" -14	M 20 x 1.5	27
<b>G HB 08 NW 13 HJL</b>	G 1/2" -14	M 22 x 1.5	27
<b>G HB 10 NW 16 HJL</b>	G 5/8" -14	M 24 x 1.5	32
<b>G HB 12 NW 20 HJL</b>	G 3/4" -14	M 30 x 1.5	37
<b>G HB 16 NW 25 HJL</b>	G 1" -11	M 33 x 1.5	41

AF = Width across flats