


| Properties | | | |
|----------------|----------------------------------|--|--|
| Connection 1 | BSP external thread, cylindrical | | |
| Sealing form 1 | 60° inner cone | | |
| Connection 2 | metric cylindrical outer thread | | |
| Sealing form 2 | 60° outer cone | | |
| Design | Screw-in sockets | | |
| Construction | straight | | |
| Material | Steel | | |
| Surface | electro galvanised | | |





| Item | | | | |
|---------------------------------------|------------|------------|------------|--|
| Identification | G1 | G2 | AF (mm) | |
| G HB 04 NW 06 HJL | G 1/4" -19 | M 14 x 1.5 | 19 | |
| G HB 06 NW 10 HJL | G 3/8" -19 | M 18 x 1.5 | 22 | |
| G HB 06 NW 13 HJL | G 3/8" -19 | M 22 x 1.5 | 22 | |
| G HB 08 NW 08 HJL 20 | G 1/2" -14 | M 20 x 1.5 | 27 | |
| G HB 08 NW 13 HJL | G 1/2" -14 | M 22 x 1.5 | 27 | |
| G HB 10 NW 16 HJL | G 5/8" -14 | M 24 x 1.5 | 32 | |
| G HB 12 NW 20 HJL | G 3/4" -14 | M 30 x 1.5 | 37 | |
| G HB 16 NW 25 HJL | G 1" -11 | M 33 x 1.5 | 41 | |
| · · · · · · · · · · · · · · · · · · · | | | | |

AF = Width across flats