

# G HB IR L

## Screw-on socket

### Properties

<b>Connection 1</b>	BSP external thread, cylindrical
<b>Sealing form 1</b>	60° inner cone
<b>Connection 2</b>	BSP cylindrical internal threads
<b>Sealing form 2</b>	Flat seal
<b>Design</b>	Screw-on socket, long
<b>Construction</b>	straight
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



### Item

Identification	G1	G2	i (mm)	L1 (mm)	AF (mm)
<b>G HB 06 IR 04 L</b>	G 3/8" -19	G 1/4" -19	12,0	30,5	22
<b>G HB 08 IR 06 L</b>	G 1/2" -14	G 3/8" -19	16,0	38,0	30
<b>G HB 16 IR 08 L</b>	G 1" -11	G 1/2" -14	19,0	50,0	41
<b>G HB 16 IR 12 L</b>	G 1" -11	G 3/4" -14	20,5	47,5	41
<b>G HB 20 IR 16 L</b>	G 1.1/4" -11	G 1" -11	20,0	48,0	50
<b>G HB 24 IR 20 L</b>	G 1.1/2" -11	G 1.1/4" -11	22,0	54,5	55

AF = Width across flats