

# G HB VA

## Connection sockets

### Properties

|                       |                                  |
|-----------------------|----------------------------------|
| <b>Connection 1</b>   | BSP external thread, cylindrical |
| <b>Sealing form 1</b> | 60° inner cone                   |
| <b>Connection 2</b>   | BSP cylindrical external threads |
| <b>Sealing form 2</b> | 60° inner cone                   |
| <b>Design</b>         | Connection sockets               |
| <b>Construction</b>   | straight                         |
| <b>Material</b>       | Stainless steel                  |



### Item

| Identification   | G1           | G2           | AF<br>(mm) |
|------------------|--------------|--------------|------------|
| G HB 02 VA       | G 1/8" -28   | G 1/8" -28   | 14         |
| G HB 02 HB 04 VA | G 1/8" -28   | G 1/4" -19   | 19         |
| G HB 02 HB 06 VA | G 1/8" -28   | G 3/8" -19   | 22         |
| G HB 04 VA       | G 1/4" -19   | G 1/4" -19   | 19         |
| G HB 04 HB 06 VA | G 1/4" -19   | G 3/8" -19   | 22         |
| G HB 04 HB 08 VA | G 1/4" -19   | G 1/2" -14   | 27         |
| G HB 04 HB 12 VA | G 1/4" -19   | G 3/4" -14   | 32         |
| G HB 06 VA       | G 3/8" -19   | G 3/8" -19   | 22         |
| G HB 06 HB 08 VA | G 3/8" -19   | G 1/2" -14   | 27         |
| G HB 06 HB 10 VA | G 3/8" -19   | G 5/8" -14   | 32         |
| G HB 06 HB 12 VA | G 3/8" -19   | G 3/4" -14   | 32         |
| G HB 06 HB 16 VA | G 3/8" -19   | G 1" -11     | 41         |
| G HB 08 VA       | G 1/2" -14   | G 1/2" -14   | 27         |
| G HB 08 HB 10 VA | G 1/2" -14   | G 5/8" -14   | 30         |
| G HB 08 HB 12 VA | G 1/2" -14   | G 3/4" -14   | 32         |
| G HB 08 HB 16 VA | G 1/2" -14   | G 1" -11     | 41         |
| G HB 08 HB 20 VA | G 1/2" -14   | G 1.1/4" -11 | 50         |
| G HB 10 VA       | G 5/8" -14   | G 5/8" -14   | 30         |
| G HB 10 HB 12 VA | G 5/8" -14   | G 3/4" -14   | 32         |
| G HB 12 VA       | G 3/4" -14   | G 3/4" -14   | 32         |
| G HB 12 HB 16 VA | G 3/4" -14   | G 1" -11     | 41         |
| G HB 12 HB 20 VA | G 3/4" -14   | G 1.1/4" -11 | 50         |
| G HB 12 HB 24 VA | G 3/4" -14   | G 1.1/2" -11 | 55         |
| G HB 16 VA       | G 1" -11     | G 1" -11     | 41         |
| G HB 16 HB 20 VA | G 1"         | G 1.1/4" -11 | 50         |
| G HB 16 HB 24 VA | G 1" -11     | G 1.1/2" -11 | 55         |
| G HB 16 HB 32 VA | G 1" -11     | G 2" -11     | 70         |
| G HB 20 VA       | G 1.1/4" -11 | G 1.1/4" -11 | 50         |
| G HB 20 HB 24 VA | G 1.1/4" -11 | G 1.1/2" -11 | 55         |
| G HB 20 HB 32 VA | G 1.1/4" -11 | G 2" -11     | 70         |
| G HB 24 VA       | G 1.1/2" -11 | G 1.1/2" -11 | 55         |
| G HB 24 HB 32 VA | G 1.1/2" -11 | G 2" -11     | 70         |
| G HB 32 VA       | G 2" -11     | G 2" -11     | 70         |

AF = Width across flats

### Product versions

|             |                           |
|-------------|---------------------------|
| <b>G HB</b> | Connection sockets, Steel |
|-------------|---------------------------|