


# G HJ HJOF

## Connection sockets

### Properties

<b>Connection 1</b>	UN/UNF external threads
<b>Sealing form 1</b>	74° outer cone
<b>Connection 2</b>	ORFS external threads
<b>Sealing form 2</b>	flat seal with O-ring
<b>Design</b>	Connection sockets
<b>Construction</b>	straight
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



### Item

Identification	G1	G2	AF (mm)	OR
<b>G HJ 04 HJOF</b>	7/16"-20 UNF	9/16"-18 UNF	16	7.65 x 1.78
<b>G HJ 05 HJOF 06</b>	1/2"-20 UNF	11/16" -16 UN	19	9.25 x 1.78
<b>G HJ 06 HJOF</b>	9/16"-18 UNF	11/16" -16 UN	19	9.25 x 1.78
<b>G HJ 08 HJOF</b>	3/4"-16 UNF	13/16" -16 UN	22	12.42 x 1.78
<b>G HJ 10 HJOF</b>	7/8" -14 UNF	1" -14 UNS	27	15.60 x 1.78
<b>G HJ 12 HJOF</b>	1.1/16" -12 UN	1.3/16" -12 UN	32	18.77 x 1.78
<b>G HJ 16 HJOF</b>	1.5/16" -12 UN	1.7/16" -12 UN	38	23.52 x 1.78
<b>G HJ 20 HJOF</b>	1.5/8" -12 UN	1.11/16" -12 UN	45	29.87 x 1.78
<b>G HJ 24 HJOF</b>	1.7/8" -12 UN	2" -12 UN	54	37.82 x 1.78

AF = Width across flats