

G HRK VA

Screw-in sockets

Properties

| | |
|-----------------------|-------------------------------|
| Connection 1 | BSPT conical external threads |
| Sealing form 1 | thread seal |
| Connection 2 | BSPT conical external threads |
| Sealing form 2 | thread seal |
| Design | Screw-in sockets |
| Construction | straight |
| Material | Stainless steel |



Item

| Identification | G1 | G2 | AF (mm) |
|-----------------------|------------|------------|------------|
| G HRK 02 VA | R 1/8" K | R 1/8" K | 11 |
| G 04 HRK 02 VA | R 1/4" K | R 1/8" K | 14 |
| G HRK 04 VA | R 1/4" K | R 1/4" K | 14 |
| G 06 HRK 04 VA | R 3/8" K | R 1/4" K | 17 |
| G HRK 06 VA | R 3/8" K | R 3/8" K | 17 |
| G 08 HRK 06 VA | R 1/2" K | R 3/8" K | 22 |
| G HRK 08 VA | R 1/2" K | R 1/2" K | 22 |
| G 12 HRK 08 VA | R 3/4" K | R 1/2" K | 27 |
| G HRK 12 VA | R 3/4" K | R 3/4" K | 27 |
| G 16 HRK 12 VA | R 1" K | R 3/4" K | 36 |
| G HRK 16 VA | R 1" K | R 1" K | 36 |
| G 20 HRK 16 VA | R 1.1/4" K | R 1" K | 46 |
| G HRK 20 VA | R 1.1/4" K | R 1.1/4" K | 25 |
| G 24 HRK 20 VA | R 1.1/2" K | R 1.1/4" K | 50 |
| G HRK 24 VA | R 1.1/2" K | R 1.1/2" K | 55 |
| G HRK 32 VA | R 2" K | R 2" K | 70 |

AF = Width across flats

Product versions

G HRK Screw-in sockets, Steel