G HRK VA

Screw-in sockets

HANSA/FLEX

Properties

•	
Connection 1	BSPT conical external threads
Sealing form 1	thread seal
Connection 2	BSPT conical external threads
Sealing form 2	thread seal
Design	Screw-in sockets
Construction	straight
Material	Stainless steel





Item Identification G1 G2 AF R 1/8" K R 1/8" K G HRK 02 VA 11 R 1/4" K R 1/8" K G 04 HRK 02 VA 14 G HRK 04 VA R 1/4" K R 1/4" K 14 G 06 HRK 04 VA R 3/8" K R 1/4" K 17 G HRK 06 VA R 3/8" K R 3/8" K 17 R 3/8" K G 08 HRK 06 VA 22 R 1/2" K 22 G HRK 08 VA R 1/2" K R 1/2" K G 12 HRK 08 VA R 3/4" K R 1/2" K 27 G HRK 12 VA R 3/4" K R 3/4" K 27 G 16 HRK 12 VA R 1" K R 3/4" K 36 G HRK 16 VA R 1" K R 1" K 36 G 20 HRK 16 VA R 1.1/4" K R 1" K 46 G HRK 20 VA R 1.1/4" K R 1.1/4" K 25 G 24 HRK 20 VA R 1.1/2" K R 1.1/4" K 50 R 1.1/2" K R 1.1/2" K G HRK 24 VA 55 R 2" K R 2" K 70 G HRK 32 VA AF = Width across flats

Product versions

G HRK Screw-in sockets, Steel