

# G IR HJ

## Connection sockets

### Properties

<b>Connection 1</b>	BSP cylindrical internal threads
<b>Sealing form 1</b>	flat sealing
<b>Connection 2</b>	UN/UNF external threads
<b>Sealing form 2</b>	74° outer cone
<b>Design</b>	Connection sockets
<b>Construction</b>	straight
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



### Item

Identification	G1	G2	AF (mm)
G IR 02 HJ 04	G 1/8" -28	7/16"-20 UNF	16
G IR 02 HJ 05	G 1/8" -28	1/2"-20 UNF	16
G IR 04 HJ	G 1/4" -19	7/16"-20 UNF	19
G IR 04 HJ 05	G 1/4" -19	1/2"-20 UNF	19
G IR 04 HJ 06	G 1/4" -19	9/16"-18 UNF	19
G IR 04 HJ 08	G 1/4" -19	3/4"-16 UNF	22
G IR 06 HJ	G 3/8" -19	9/16"-18 UNF	22
G IR 06 HJ 08	G 3/8" -19	3/4"-16 UNF	22
G IR 08 HJ 06	G 1/2" -14	9/16"-18 UNF	30
G IR 08 HJ	G 1/2" -14	3/4"-16 UNF	30
G IR 08 HJ 10	G 1/2" -14	7/8"-14 UNF	30
G IR 08 HJ 12	G 1/2" -14	1.1/16" -12 UN	30
G IR 12 HJ 08	G 3/4" -14	3/4"-16 UNF	36
G IR 12 HJ	G 3/4" -14	1.1/16" -12 UN	36
G IR 12 HJ 14	G 3/4" -14	1.3/16" -12 UN	41
G IR 16 HJ	G 1" -11	1.5/16" -12 UN	46
G IR 16 HJ 20	G 1" -11	1.5/8" -12 UN	50
G IR 20 HJ	G 1.1/4" -11	1.5/8" -12 UN	50
G IR 20 HJ 24	G 1.1/4" -11	1.7/8" -12 UN	55
G IR 24 HJ	G 1.1/2" -11	1.7/8" -12 UN	55
G IR 32 HJ	G 2" -11	2.1/2" -12 UN	73

AF = Width across flats