

GE HMO HJ

Screw-in sockets

Properties

| | |
|-----------------------|---------------------------------|
| Connection 1 | metric cylindrical outer thread |
| Sealing form 1 | O-ring seal on screw-in socket |
| Connection 2 | UN/UNF external threads |
| Sealing form 2 | 74° outer cone |
| Design | Screw-in sockets |
| Construction | straight |
| Material | Steel |
| Surface | electro galvanised |



| Item | | | | |
|-----------------|------------|----------------|------------|------------|
| Identification | G1 | G2 | AF (mm) | OR |
| GE HMO 10 HJ 04 | M 10 x 1 | 7/16"-20 UNF | 14 | 8.1 x 1.6 |
| GE HMO 10 HJ 05 | M 10 x 1 | 1/2"-20 UNF | 14 | 8.1 x 1.6 |
| GE HMO 12 HJ 04 | M 12 x 1.5 | 7/16"-20 UNF | 17 | 9.3 x 2.2 |
| GE HMO 12 HJ 05 | M 12 x 1.5 | 1/2"-20 UNF | 17 | 9.3 x 2.2 |
| GE HMO 14 HJ 05 | M 14 x 1.5 | 1/2"-20 UNF | 19 | 11.3 x 2.2 |
| GE HMO 14 HJ 06 | M 14 x 1.5 | 9/16"-18 UNF | 19 | 11.3 x 2.2 |
| GE HMO 14 HJ 08 | M 14 x 1.5 | 3/4"-16 UNF | 19 | 11.3 x 2.2 |
| GE HMO 16 HJ 06 | M 16 x 1.5 | 9/16"-18 UNF | 22 | 13.3 x 2.2 |
| GE HMO 16 HJ 08 | M 16 x 1.5 | 3/4"-16 UNF | 22 | 13.3 x 2.2 |
| GE HMO 18 HJ 06 | M 18 x 1.5 | 9/16"-18 UNF | 24 | 15.3 x 2.2 |
| GE HMO 18 HJ 08 | M 18 x 1.5 | 3/4"-16 UNF | 24 | 15.3 x 2.2 |
| GE HMO 18 HJ 10 | M 18 x 1.5 | 7/8"-14 UNF | 24 | 15.3 x 2.2 |
| GE HMO 22 HJ 10 | M 22 x 1.5 | 7/8"-14 UNF | 27 | 19.3 x 2.2 |
| GE HMO 22 HJ 12 | M 22 x 1.5 | 1.1/16" -12 UN | 27 | 19.3 x 2.2 |
| GE HMO 27 HJ 12 | M 27 x 2 | 1.1/16" -12 UN | 32 | 23.6 x 2.9 |
| GE HMO 27 HJ 16 | M 27 x 2 | 1.5/16" -12 UN | 36 | 23.6 x 2.9 |
| GE HMO 33 HJ 16 | M 33 x 2 | 1.5/16" -12 UN | 41 | 29.6 x 2.9 |
| GE HMO 42 HJ 20 | M 42 x 2 | 1.5/8" -12 UN | 50 | 38.6 x 2.9 |
| GE HMO 48 HJ 24 | M 48 x 2 | 1.7/8" -12 UN | 55 | 44.6 x 2.9 |

AF = Width across flats