


Properties							
Connection 1	NPT external threads						
Sealing form 1	thread seal						
Connection 2	BSP nut thread						
Sealing form 2	60° inner cone						
Design	Screw-in sockets						
Construction	straight						
Material	Steel						
Surface	electro galvanised						





Item				
Identification	G1	G2	AF (mm)	S1
GE HN 04 AB	1/4" -18 NPT	G 1/4" -19	16	19
GE HN 04 AB 06	1/4" -18 NPT	G 3/8" -19	18	22
GE HN 06 AB 04	3/8" -18 NPT	G 1/4" -19	21	19
GE HN 06 AB	3/8" -18 NPT	G 3/8" -19	22	22
GE HN 06 AB 08	3/8" -18 NPT	G 1/2" -14	25	22
GE HN 08 AB 06	1/2" -14 NPT	G 3/8" -19	22	22
GE HN 08 AB	1/2" -14 NPT	G 1/2" -14	25	27
GE HN 08 AB 10	1/2" -14 NPT	G 5/8" -14	27	30
GE HN 12 AB 08	3/4" -14 NPT	G 1/2" -14	33	27
GE HN 12 AB	3/4" -14 NPT	G 3/4" -14	33	32
GE HN 16 AB	1" -11.5 NPT	G 1" -11	38	41
GE HN 16 AB 12	1" -11.5 NPT	G 3/4" -14	35	32

SW, S1, S2 = With across flats

$\overline{}$.1		- 4					
М	ro	a	u	CI	ve	rsı	Ю	n	S

GE HN AB VA Screw-in sockets, Stainless steel