
# GE HN IR VA
Screw-in sockets

HANSA-FLEX

## Properties

| | |
|---|---|
| **Connection 1** | NPT external threads |
| **Sealing form 1** | thread seal |
| **Connection 2** | BSP cylindrical internal threads |
| **Sealing form 2** | Flat seal |
| **Design** | Screw-in sockets |
| **Construction** | straight |
| **Material** | Stainless steel |






## Item

| Identification | G1 | G2 | AF (mm) |
|---|---|---|---|
| **GE HN 02 IR VA** | 1/8" -27 NPT | G 1/8" -28 | 14 |
| **GE HN 02 IR 04 VA** | 1/8" -27 NPT | G 1/4" -19 | 19 |
| **GE HN 04 IR 02 VA** | 1/4" -18 NPT | G 1/8" -28 | 14 |
| **GE HN 04 IR VA** | 1/4" -18 NPT | G 1/4" -19 | 19 |
| **GE HN 04 IR 06 VA** | 1/4" -18 NPT | G 3/8" -19 | 24 |
| **GE HN 04 IR 08 VA** | 1/4" -18 NPT | G 1/2" -14 | 27 |
| **GE HN 06 IR 04 VA** | 3/8" -18 NPT | G 1/4" -19 | 19 |
| **GE HN 06 IR VA** | 3/8" -18 NPT | G 3/8" -19 | 24 |
| **GE HN 06 IR 08 VA** | 3/8" -18 NPT | G 1/2" -14 | 27 |
| **GE HN 08 IR 04 VA** | 1/2" -14 NPT | G 1/4" -19 | 24 |
| **GE HN 08 IR 06 VA** | 1/2" -14 NPT | G 3/8" -19 | 24 |
| **GE HN 08 IR VA** | 1/2" -14 NPT | G 1/2" -14 | 27 |
| **GE HN 08 IR 12 VA** | 1/2" -14 NPT | G 3/4" -14 | 32 |
| **GE HN 12 IR 06 VA** | 3/4" -14 NPT | G 3/8" -19 | 27 |
| **GE HN 12 IR 08 VA** | 3/4" -14 NPT | G 1/2" -14 | 27 |
| **GE HN 12 IR VA** | 3/4" -14 NPT | G 3/4" -14 | 32 |
| **GE HN 12 IR 16 VA** | 3/4" -14 NPT | G 1" -11 | 41 |
| **GE HN 16 IR 08 VA** | 1" -11.5 NPT | G 1/2" -14 | 36 |
| **GE HN 16 IR 12VA** | 1" -11.5 NPT | G 3/4" -14 | 36 |
| **GE HN 16 IR VA** | 1" -11.5 NPT | G 1" -11 | 41 |
| **GE HN 20 IR VA** | 1.1/4" -11.5 NPT | G 1.1/4" -11 | 55 |
| **GE HN 24 IR VA** | 1.1/2" -11.5 NPT | G 1.1/2" -11 | 55 |

AF = Width across flats

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*