
# GE HRED HJ VA
Screw-in sockets

## Properties

| | |
|---|---|
| **Connection 1** | BSP external thread, cylindrical |
| **Sealing form 1** | Shape E |
| **Connection 2** | UN/UNF external threads |
| **Sealing form 2** | 74° outer cone |
| **Design** | Screw-in sockets |
| **Construction** | straight |
| **Material** | Stainless steel |






## Ordering information

Seals of NBR
FPM (Viton) on request

## Item

| Identification | G1 | G2 | AF (mm) |
|---|---|---|---|
| **GE HRED 02 HJ 04 VA** | G 1/8" -28 | 7/16"-20 UNF | 14 |
| **GE HRED 04 HJ 05 VA** | G 1/4" -19 | 1/2"-20 UNF | 19 |
| **GE HRED 04 HJ 06 VA** | G 1/4" -19 | 9/16"-18 UNF | 19 |
| **GE HRED 04 HJ 08 VA** | G 1/4" -19 | 3/4"-16 UNF | 19 |
| **GE HRED 04 HJ VA** | G 1/4" -19 | 7/16"-20 UNF | 19 |
| **GE HRED 06 HJ 04 VA** | G 3/8" -19 | 7/16"-20 UNF | 22 |
| **GE HRED 06 HJ 05 VA** | G 3/8" -19 | 1/2"-20 UNF | 22 |
| **GE HRED 06 HJ 08 VA** | G 3/8" -19 | 3/4"-16 UNF | 22 |
| **GE HRED 06 HJ VA** | G 3/8" -19 | 9/16"-18 UNF | 22 |
| **GE HRED 08 HJ 06VA** | G 1/2" -14 | 9/16"-18 UNF | 27 |
| **GE HRED 08 HJ 10 VA** | G 1/2" -14 | 7/8"-14 UNF | 27 |
| **GE HRED 08 HJ 12 VA** | G 1/2" -14 | 1.1/16" -12 UN | 27 |
| **GE HRED 08 HJ VA** | G 1/2" -14 | 3/4"-16 UNF | 27 |
| **GE HRED 12 HJ 10 VA** | G 3/4" -14 | 7/8"-14 UNF | 32 |
| **GE HRED 12 HJ 16 VA** | G 3/4" -14 | 1.5/16" -12 UN | 36 |
| **GE HRED 12 HJ VA** | G 3/4" -14 | 1.1/16" -12 UN | 32 |
| **GE HRED 16 HJ 20 VA** | G 1" -11 | 1.5/8" -12 UN | 46 |
| **GE HRED 16 HJ VA** | G 1" -11 | 1.5/16" -12 UN | 41 |
| **GE HRED 20 HJ 24 VA** | G 1.1/4" -11 | 1.7/8" -12 UN | 50 |
| **GE HRED 20 HJ VA** | G 1.1/4" -11 | 1.5/8" -12 UN | 50 |
| **GE HRED 24 HJ VA** | G 1.1/2" -11 | 1.7/8" -12 UN | 55 |

AF = Width across flats

## Product versions

| | |
|---|---|
| **GE HRED HJ** | Screw-in sockets, Steel |

## Spare parts

| | |
|---|---|
| **WD V** | Soft seal for ED fittings |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*