

# GE HRED HJOF VA

Screw-in sockets

## Properties

<b>Connection 1</b>	BSP external thread, cylindrical
<b>Sealing form 1</b>	Shape E
<b>Connection 2</b>	ORFS external threads
<b>Sealing form 2</b>	flat seal with O-ring
<b>Design</b>	Screw-in sockets
<b>Construction</b>	straight
<b>Material</b>	Stainless steel



## Ordering information

Seals of NBR  
FPM (Viton) on request

Item	G1	G2	AF (mm)	OR
GE HRED 02 HJOF 04 VA	G 1/8" -28	9/16" -18 UNF	17	7.65 x 1.78
GE HRED 02 HJOF06 VA	G 1/8" -28	11/16" -16 UN	19	9.25 x 1.78
GE HRED 04 HJOF 06 VA	G 1/4" -19	11/16" -16 UN	19	9.25 x 1.78
GE HRED 04 HJOF 08 VA	G 1/4" -19	13/16" -16 UN	22	12.42 x 1.78
GE HRED 04 HJOF VA	G 1/4" -19	9/16" -18 UNF	19	7.65 x 1.78
GE HRED 06 HJOF 04 VA	G 3/8" -19	9/16" -18 UNF	22	7.65 x 1.78
GE HRED 06 HJOF 08 VA	G 3/8" -19	13/16" -16 UN	22	12.42 x 1.78
GE HRED 06 HJOF 10 VA	G 3/8" -19	1" -14 UNS	27	15.60 x 1.78
GE HRED 06 HJOF VA	G 3/8" -19	11/16" -16 UN	22	9.25 x 1.78
GE HRED 08 HJOF 06 VA	G 1/2" -14	11/16" -16 UN	27	9.25 x 1.78
GE HRED 08 HJOF 10 VA	G 1/2" -14	1" -14 UNS	27	15.60 x 1.78
GE HRED 08 HJOF 12 VA	G 1/2" -14	1.3/16" -12 UN	32	18.77 x 1.78
GE HRED 08 HJOF VA	G 1/2" -14	13/16" -16 UN	27	12.42 x 1.78
GE HRED 12 HJOF 10 VA	G 3/4" -14	1" -14 UNS	32	15.60 x 1.78
GE HRED 12 HJOF 16 VA	G 3/4" -14	1.7/16" -12 UN	41	23.52 x 1.78
GE HRED 12 HJOF VA	G 3/4" -14	1.3/16" -12 UN	32	18.77 x 1.78
GE HRED 16 HJOF VA	G 1" -11	1.7/16" -12 UN	41	23.52 x 1.78

AF = Width across flats

## Product versions

GE HRED HJOF Screw-in sockets, Steel

## Spare parts

WD V Soft seal for ED fittings