GE HRK HJ VA

Screw-in sockets

HANSA/FLEX

Properties

Connection 1	BSPT conical external threads		
Sealing form 1	thread seal		
Connection 2	UN/UNF external threads		
Sealing form 2	74° outer cone		
Design	Screw-in sockets		
Construction	straight		
Material	Stainless steel		





Item

Identification	G1	G2	AF	
			(mm)	
GE HRK 02 HJ 04 VA	R 1/8" K	7/16"-20 UNF	13	
GE HRK 04 HJ VA	R 1/4" K	7/16"-20 UNF	14	
GE HRK 04 HJ 05 VA	R 1/4" K	1/2"-20 UNF	14	
GE HRK 04 HJ 06 VA	R 1/4" K	9/16"-18 UNF	16	
GE HRK 06 HJ VA	R 3/8" K	9/16"-18 UNF	19	
GE HRK 06 HJ 08 VA	R 3/8" K	3/4"-16 UNF	19	
GE HRK 08 HJ 06 VA	R 1/2" K	9/16"-18 UNF	22	
GE HRK 08 HJ VA	R 1/2" K	3/4"-16 UNF	22	
GE HRK 08 HJ 10 VA	R 1/2" K	7/8"-14 UNF	24	
GE HRK 12 HJ VA	R 3/4" K	1.1/16" -12 UN	27	

AF = Width across flats

Product versions

GE HRK HJ Screw-in sockets, Steel