

Properties

| | |
|----------------|--------------------------------|
| Connection 1 | UN/UNF external threads |
| Sealing form 1 | O-ring seal on screw-in socket |
| Connection 2 | UN/UNF external threads |
| Sealing form 2 | 74° outer cone |
| Design | Screw-in sockets |
| Construction | straight |
| Material | Steel |
| Surface | electro galvanised |



Item

| Identification | G1 | G2 | AF (mm) | OR |
|----------------|----------------|----------------|------------|--------------|
| GE O 03 HJ 04 | 3/8"-24 UNF | 7/16"-20 UNF | 12 | 7.65 x 1.78 |
| GE O 04 HJ | 7/16"-20 UNF | 7/16"-20 UNF | 14 | 8.92 x 1.83 |
| GE O 04 HJ 05 | 7/16"-20 UNF | 1/2"-20 UNF | 14 | 8.92 x 1.83 |
| GE O 04 HJ 06 | 7/16"-20 UNF | 9/16"-18 UNF | 17 | 8.92 x 1.83 |
| GE O 05 HJ 04 | 1/2"-20 UNF | 7/16"-20 UNF | 17 | 10.52 x 1.83 |
| GE O 05 HJ | 1/2"-20 UNF | 1/2"-20 UNF | 17 | 10.52 x 1.83 |
| GE O 05 HJ 06 | 1/2"-20 UNF | 9/16"-18 UNF | 17 | 10.52 x 1.83 |
| GE O 06 HJ 04 | 9/16"-18 UNF | 7/16"-20 UNF | 17 | 11.90 x 1.98 |
| GE O 06 HJ 05 | 9/16"-18 UNF | 1/2"-20 UNF | 17 | 11.90 x 1.98 |
| GE O 06 HJ | 9/16"-18 UNF | 9/16"-18 UNF | 17 | 11.90 x 1.98 |
| GE O 06 HJ 08 | 9/16"-18 UNF | 3/4"-16 UNF | 19 | 11.90 x 1.98 |
| GE O 08 HJ 04 | 3/4"-16 UNF | 7/16"-20 UNF | 22 | 16.36 x 2.20 |
| GE O 08 HJ 05 | 3/4"-16 UNF | 1/2"-20 UNF | 22 | 16.36 x 2.20 |
| GE O 08 HJ 06 | 3/4"-16 UNF | 9/16"-18 UNF | 22 | 16.36 x 2.20 |
| GE O 08 HJ | 3/4"-16 UNF | 3/4"-16 UNF | 22 | 16.36 x 2.20 |
| GE O 08 HJ 10 | 3/4"-16 UNF | 7/8"-14 UNF | 24 | 16.36 x 2.20 |
| GE O 08 HJ 12 | 3/4"-16 UNF | 1.1/16" -12 UN | 27 | 16.36 x 2.20 |
| GE O 10 HJ 08 | 7/8" -14 UNF | 3/4"-16 UNF | 27 | 19.18 x 2.46 |
| GE O 10 HJ 06 | 7/8" -14 UNF | 9/16"-18 UNF | 27 | 19.18 x 2.46 |
| GE O 10 HJ | 7/8" -14 UNF | 7/8"-14 UNF | 27 | 19.18 x 2.46 |
| GE O 10 HJ 12 | 7/8" -14 UNF | 1.1/16" -12 UN | 27 | 19.18 x 2.46 |
| GE O 10 HJ 16 | 7/8" -14 UNF | 1.5/16" -12 UN | 36 | 19.18 x 2.46 |
| GE O 12 HJ 06 | 1.1/16" -12 UN | 9/16"-18 UNF | 32 | 23.47 x 2.95 |
| GE O 12 HJ 08 | 1.1/16" -12 UN | 3/4"-16 UNF | 32 | 23.47 x 2.95 |
| GE O 12 HJ 10 | 1.1/16" -12 UN | 7/8"-14 UNF | 32 | 23.47 x 2.95 |
| GE O 12 HJ | 1.1/16" -12 UN | 1.1/16" -12 UN | 32 | 23.47 x 2.95 |
| GE O 12 HJ 16 | 1.1/16" -12 UN | 1.5/16" -12 UN | 36 | 23.47 x 2.95 |
| GE O 14 HJ 12 | 1.3/16" -12 UN | 1.1/16" -12 UN | 36 | 26.59 x 2.95 |
| GE O 14 HJ | 1.3/16" -12 UN | 1.3/16" -12 UN | 36 | 26.59 x 2.95 |
| GE O 16 HJ 10 | 1.5/16" -12 UN | 7/8"-14 UNF | 41 | 29.74 x 2.95 |
| GE O 16 HJ 12 | 1.5/16" -12 UN | 1.1/16" -12 UN | 41 | 29.74 x 2.95 |
| GE O 16 HJ | 1.5/16" -12 UN | 1.5/16" -12 UN | 41 | 29.74 x 2.95 |
| GE O 16 HJ 20 | 1.5/16" -12 UN | 1.5/8" -12 UN | 46 | 29.74 x 2.95 |
| GE O 16 HJ 24 | 1.5/16" -12 UN | 1.7/8" -12 UN | 50 | 29.74 x 2.95 |
| GE O 20 HJ 16 | 1.5/8" -12 UN | 1.5/16" -12 UN | 50 | 37.47 x 3.00 |
| GE O 20 HJ | 1.5/8" -12 UN | 1.5/8" -12 UN | 50 | 37.47 x 3.00 |
| GE O 20 HJ 24 | 1.5/8" -12 UN | 1.7/8" -12 UN | 50 | 37.47 x 3.00 |
| GE O 24 HJ 20 | 1.7/8" -12 UN | 1.5/8" -12 UN | 55 | 43.69 x 3.00 |
| GE O 24 HJ | 1.7/8" -12 UN | 1.7/8" -12 UN | 55 | 43.69 x 3.00 |
| GE O 32 HJ | 2.1/2" -12 UN | 2.1/2" -12 UN | 70 | 43.69 x 3.00 |

AF = Width across flats

Product versions

GE O HJ VA Screw-in sockets, Stainless steel