
# GE O IN
Screw-on fitting

HANSA-FLEX

## Properties

| | |
|---|---|
| **Connection 1** | UN/UNF external threads |
| **Sealing form 1** | O-ring seal on screw-in socket |
| **Connection 2** | NPT internal thread |
| **Sealing form 2** | thread seal |
| **Design** | Screw-on fitting |
| **Construction** | straight |
| **Material** | Steel |
| **Surface** | electro galvanised |






## Item

| Identification | G1 | G2 | AF (mm) | OR |
|---|---|---|---|---|
| **GE O 06 IN 04** | 9/16"-18 UNF | 1/4" -18 NPT | 19 | 11.90 x 1.98 |
| **GE O 08 IN 04** | 3/4"-16 UNF | 1/4" -18 NPT | 22 | 16.36 x 2.20 |
| **GE O 08 IN 06** | 3/4"-16 UNF | 3/8" -18 NPT | 22 | 16.36 x 2.20 |
| **GE O 08 IN** | 3/4"-16 UNF | 1/2" -14 NPT | 29 | 16.36 x 2.20 |
| **GE O 10 IN 04** | 7/8" -14 UNF | 1/4" -18 NPT | 25 | 19.18 x 2.46 |
| **GE O 10 IN 06** | 7/8" -14 UNF | 3/8" -18 NPT | 25 | 19.18 x 2.46 |
| **GE O 10 IN 08** | 7/8" -14 UNF | 1/2" -14 NPT | 29 | 19.18 x 2.46 |
| **GE O 12 IN 08** | 1.1/16" -12 UN | 1/2" -14 NPT | 32 | 23.47 x 2.95 |
| **GE O 12 IN** | 1.1/16" -12 UN | 3/4" -14 NPT | 35 | 23.47 x 2.95 |

AF = Width across flats

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*