

# WEO SB HL / WEO SB HS

WEO socket

**HANSA FLEX**

## Properties

<b>Connection 1</b>	WEO socket
<b>Sealing form 1</b>	O-ring seal
<b>Connection 2</b>	metric cylindrical outer thread
<b>Sealing form 2</b>	24° inner cone
<b>Material</b>	Steel



## Item

Identification	Series	Ø d2 (mm)	Size	Operating pressure	G1	Ø D1 (mm)	L1 (mm)	S1
WEO 10 SB NW 06 HL	L	8	1/4"	PN 250	M 14 x 1.5	10	36	19
WEO 13 SB NW 10 HL	L	12	3/8"	PN 250	M 18 x 1.5	13	40	22
WEO 16 SB NW 13 HL	L	15	1/2"	PN 250	M 22 x 1.5	16	41	27
WEO 23 SB NW 20 HL	L	22	3/4"	PN 160	M 30 x 2	23	54	32
WEO 13 SB NW 08 HS	S	12	3/8"	PN 350	M 20 x 1.5	13	41	22
WEO 16 SB NW 13 HS	S	16	1/2"	PN 350	M 24 x 1.5	16	43	27
WEO 23 SB NW 20 HS	S	25	3/4"	PN 250	M 36 x 2	23	58	41

Ø d2 = External pipe diameter – SW, S1, S2 = With across flats

## Spare parts

<b>WEO B DISA</b>	WEO sealing set
-------------------	-----------------