

# WEO SB O

WEO socket

**HANSA FLEX**

## Properties

<b>Connection 1</b>	WEO socket
<b>Sealing form 1</b>	O-ring seal
<b>Connection 2</b>	UN/UNF external threads
<b>Sealing form 2</b>	Shape F
<b>Material</b>	Steel



## Item

Identification	Size	Operating pressure	G1	Ø D1 (mm)	i (mm)	L1 (mm)	S1	OR
<b>WEO 10 SB O 04</b>	1/4"	PN 350	7/16"-20 UNF	10	9	35	19	8.92 x 1.83
<b>WEO 13 SB O 06</b>	3/8"	PN 350	9/16"-18 UNF	13	10	39	22	11.90 x 1.98
<b>WEO 16 SB O 08</b>	1/2"	PN 350	3/4"-16 UNF	16	11	40	27	16.36 x 2.20
<b>WEO 23 SB O 12</b>	3/4"	PN 350	1.1/16" -12 UN	23	15	55	32	23.47 x 2.95
<b>WEO 30 SB O 16</b>	1"	PN 250	1.5/16" -12 UN	30	15	64	41	29.74 x 2.95

SW, S1, S2 = With across flats

## Spare parts

<b>WEO B DISA</b>	WEO sealing set
-------------------	-----------------