
AVX
Wound hose for exhaust gases

HANSA-FLEX

Properties

Application	Highly suitable for conveying exhaust gases
Design	wound metal hose with metallic seal multi-edged polygonal design
Properties	Special winding technology assures very low leakage and exceptional flexibility
Temp. range	can be used up to 400 °C
Material	Galvanised steel band





Note

Wound hoses are stretched for measurement.

Ordering information

Other sizes on request

Item

Identification	Ø ID (mm)	Ø AD (mm)	Tolerances of ID/ED (mm)	Bending radius (+10 %) (mm)	Weight compressed (per m) (kg)
AVX 020	20,00	23,00	0,40	115	0,46
AVX 025	25,00	28,00	0,40	140	0,58
AVX 030	30,00	33,50	0,40	150	0,70
AVX 032	32,00	35,50	0,40	160	0,84
AVX 035	35,00	38,50	0,40	173	0,92
AVX 040	40,00	43,50	0,40	182	1,05
AVX 045	45,00	48,50	0,40	192	1,18
AVX 050	50,00	54,00	0,40	205	1,63
AVX 055	55,00	59,00	0,40	225	1,80
AVX 060	60,00	64,00	0,40	234	1,94
AVX 065	65,00	69,00	0,40	254	2,15
AVX 070	70,00	74,00	0,40	273	2,30
AVX 075	75,00	79,00	0,40	293	2,43
AVX 080	80,00	84,00	0,60	312	2,62
AVX 085	85,00	89,00	0,60	332	2,76
AVX 090	90,00	94,00	0,60	351	2,90
AVX 096	96,00	100,00	0,60	375	3,10
AVX 100	100,00	104,00	0,80	390	3,25
AVX 110	110,00	114,00	0,80	429	3,55
AVX 115	115,00	119,00	0,80	449	3,74
AVX 120	120,00	124,00	0,80	468	3,92
AVX 125	125,00	129,00	0,80	488	4,06
AVX 130	130,00	135,00	0,80	620	5,08
AVX 140	140,00	145,00	1,00	680	5,48
AVX 150	150,00	155,00	1,00	715	5,88
AVX 200	200,00	205,00	1,00	950	7,80

Product versions

KAX	Wound hose for exhaust gases, Stainless steel strip 1.4301

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.