




<b>Properties</b>					
Application	Coolant and lubricant lines for metal chipping processes.				
Design	Steel support helix with PVC inner hose Inlet side: Screw-in pin Outlet side: Steel discharge nozzle Surface nickel-plated				
Properties	Completely tight can be bent into almost any position by hand tough resistant to oils, greases etc.				





## **Ordering information**

Other sizes on request

Item					
Identification	G1	ID .	S1	Nominal length (+/-5 mm)	
NIAC 4/0 200	R 1/8"	(mm)	(mm)	200	
NIAG 1/8-200	R 1/8"	8,0	15,0		
NIAG 1/8-250		8,0	15,0	250	
NIAG 1/8-320	R 1/8"	8,0	15,0	320	
NIAG 1/8-400	R 1/8"	8,0	15,0	400	
NIAG 1/8-500	R 1/8"	8,0	15,0	500	
NIAG 1/8-630	R 1/8"	8,0	15,0	630	
NIAG 1/8-800	R 1/8"	8,0	15,0	800	
NIAG 1/4-200	R 1/4"	10,0	19,0	200	
NIAG 1/4-250	R 1/4"	10,0	19,0	250	
NIAG 1/4-320	R 1/4"	10,0	19,0	320	
NIAG 1/4-400	R 1/4"	10,0	19,0	400	
NIAG 1/4-500	R 1/4"	10,0	19,0	500	
NIAG 1/4-630	R 1/4"	10,0	19,0	630	
NIAG 1/4-800	R 1/4"	10,0	19,0	800	
NIAG 3/8-250	R 3/8"	10,0	24,0	250	
NIAG 3/8-300	R 3/8"	10,0	24,0	300	
NIAG 3/8-320	R 3/8"	10,0	24,0	320	
NIAG 3/8-400	R 3/8"	10,0	24,0	400	
NIAG 3/8-500	R 3/8"	10,0	24,0	500	
NIAG 3/8-630	R 3/8"	10,0	24,0	630	
NIAG 3/8-800	R 3/8"	10,0	24,0	800	
NIAG 1/2-250	R 1/2"	12,0	27,0	250	
NIAG 1/2-320	R 1/2"	12,0	27,0	320	
NIAG 1/2-400	R 1/2"	12,0	27,0	400	
NIAG 1/2-500	R 1/2"	12,0	27,0	500	
NIAG 1/2-630	R 1/2"	12,0	27,0	630	
NIAG 1/2-800	R 1/2"	12,0	27,0	800	