

# DAMPF B

Steam hose

**HANSA FLEX**

## Properties

<b>Application</b>	Hot water or saturated steam applications
<b>Special features</b>	electrically conductive
<b>Standard</b>	ISO 6134 TYPE2, CLASS:A
<b>Inner layer</b>	EPDM
<b>Insert</b>	two steel wire braided inserts
<b>Outer layer</b>	EPDM (patterned material)
<b>Colour</b>	black
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	210 °C
<b>Media</b>	Steam Hot water



## Note

Please observe the guidelines of BG CHEMIE T002; Hose lines - safe application / 6.3.3 Additional notes for the use of hose lines for steam and hot water.

Bleed water or steam after use.

Appropriate hose fittings on request.

## Item

Identification	Internal Ø (mm)	External Ø (mm)	Wall thickness (mm)	Operating pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)	Roll length (m)
<b>DAMPF 13-6 B</b>	12,7	25	6,0	18,0	180	130	40
<b>DAMPF 16-6 B</b>	16,0	29	6,5	18,0	180	160	40
<b>DAMPF 19-6 B</b>	19,0	33	7,0	18,0	180	190	40
<b>DAMPF 25-6.5 B</b>	25,4	40	7,5	18,0	180	250	40
<b>DAMPF 32-7 B</b>	32,0	48	8,0	18,0	180	320	40
<b>DAMPF 38-8 B</b>	38,0	54	8,0	18,0	180	380	40
<b>DAMPF 50-9 B</b>	50,8	69	9,0	18,0	180	500	40