

DAMPF B

Steam hose

HANSA FLEX

Properties

Application	Hot water or saturated steam applications
Special features	electrically conductive
Standard	ISO 6134 TYPE2, CLASS:A
Inner layer	EPDM
Insert	two steel wire braided inserts
Outer layer	EPDM (patterned material)
Colour	black
Temp. min.	-40 °C
Temp. max.	210 °C
Media	Steam Hot water



Note

Please observe the guidelines of BG CHEMIE T002; Hose lines - safe application / 6.3.3 Additional notes for the use of hose lines for steam and hot water.

Bleed water or steam after use.

Appropriate hose fittings on request.

Item

Identification	Internal Ø (mm)	External Ø (mm)	Wall thickness (mm)	Operating pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)	Roll length (m)
DAMPF 13-6 B	12,7	25	6,0	18,0	180	130	40
DAMPF 16-6 B	16,0	29	6,5	18,0	180	160	40
DAMPF 19-6 B	19,0	33	7,0	18,0	180	190	40
DAMPF 25-6.5 B	25,4	40	7,5	18,0	180	250	40
DAMPF 32-7 B	32,0	48	8,0	18,0	180	320	40
DAMPF 38-8 B	38,0	54	8,0	18,0	180	380	40
DAMPF 50-9 B	50,8	69	9,0	18,0	180	500	40