Steam hose



Properties					
Application	Hot water or saturated steam applications				
Special features	electrically conductive				
Standard	ISO 6134 TYPE2, CLASS:A				
Inner layer	EPDM				
Insert	two steel wire braided inserts				
Outer layer	EPDM (patterned material)				
Colour	black				
Temp. min.	-40 °C				
Temp. max.	210 °C				
Media	Steam Hot water				



Note

Please observe the guidelines of BG CHEMIE T002; Hose lines - safe application / 6.3.3 Additional notes for the use of hose lines for steam and hot water.

Bleed water or steam after use.

Appropriate hose fittings on request.

Item									
Identification	Internal Ø	External Ø	Wall thickness	Operating pressure (bar)	Burst pressure	Min. bending radius	Roll length		
DAMPF 13-6 B	12,7	25	6,0	18,0	180	130	40		
DAMPF 16-6 B	16,0	29	6,5	18,0	180	160	40		
DAMPF 19-6 B	19,0	33	7,0	18,0	180	190	40		
DAMPF 25-6.5 B	25,4	40	7,5	18,0	180	250	40		
DAMPF 32-7 B	32,0	48	8,0	18,0	180	320	40		
DAMPF 38-8 B	38,0	54	8,0	18,0	180	380	40		
DAMPF 50-9 B	50,8	69	9,0	18,0	180	500	40		