

# HD 200 (2SN)

HD hose

**HANSA-FLEX**

## Properties

<b>Application</b>	medium high pressure circuits
<b>Standard</b>	EN 853 2 SN
<b>Inner layer</b>	oil resistant synthetic rubber
<b>Insert</b>	two high tensile steel wire braided inserts
<b>Outer layer</b>	synthetic rubber with high temperature, ozone and weather resistance
<b>Colour</b>	black
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	100 °C
<b>Elongation</b>	+ 2 % to - 4 %
<b>Media</b>	Mineral oil Polyglycol based oil Water (0°C to + 70°C) Water-oil emulsions



## Note

The change in length of the hose is determined at max. working pressure during testing to EN ISO 1402.

## Item

Identification	DN*	Size	Inches	Internal Ø min. (mm)	Internal Ø max. (mm)	Ø Insert min. (mm)	Ø Insert max. (mm)	External Ø max. (mm)	Operating pressure (bar)	Test pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)
HD 204	5	3	3/16"	4,6	5,4	10,6	11,6	14,1	415,0	830	1650	90
HD 206	6	4	1/4"	6,2	7,0	12,1	13,3	15,7	400,0	800	1600	100
HD 208	8	5	5/16"	7,7	8,5	13,7	14,9	17,3	350,0	700	1400	115
HD 210	10	6	3/8"	9,3	10,1	16,1	17,3	19,7	330,0	660	1320	130
HD 213	12	8	1/2"	12,3	13,5	19,0	20,6	23,0	275,0	550	1100	180
HD 216	16	10	5/8"	15,5	16,7	22,2	23,8	26,2	250,0	500	1000	200
HD 220	19	12	3/4"	18,6	19,8	26,2	27,8	30,1	215,0	430	850	240
HD 225	25	16	1"	25,0	26,4	34,1	35,7	38,9	165,0	325	650	300
HD 232	31	20	1.1/4"	31,4	33,0	43,3	45,7	49,5	125,0	250	500	420
HD 240	38	24	1.1/2"	37,7	39,3	49,6	52,0	55,9	90,0	180	360	500
HD 250	51	32	2"	50,4	52,0	62,3	64,7	68,6	80,0	160	320	630
HD 260	60	40	2.3/8"	59,6	61,2	67,4	70,2	73,1	90,0	180	360	630
HD 276	76	48	3"	75,6	77,2	85,4	88,4	92,6	45,0	90	180	912

DN = Nominal diameter, nominal width