# HW 200 (2SN)
Hot water hose

## Properties

| | |
|---|---|
| **Application** | High pressure cleaning equipment |
| **Standard** | EN 853 2 SN |
| **Inner layer** | water, oil and heat resistant synthetic rubber |
| **Insert** | two high tensile steel wire braided inserts |
| **Outer layer** | environmentally safe synthetic rubber |
| **Colour** | black |
| **Temp. min.** | -10 °C |
| **Temp. max.** | 150 °C |
| **Elongation** | + 2 % to - 4 % |
| **Media** | Water<br>Mineral oil (up to + 100°C)<br>Water-oil emulsions |




## Note

The change in length of the hose is determined at max. working pressure during testing to EN ISO 1402.

## Item

| Identification | DN* | Inches | Size | Internal Ø (mm) | External Ø (mm) | Operating pressure (bar) | Burst pressure (bar) | Min. bending radius (mm) |
|---|---|---|---|---|---|---|---|---|
| **HW 206** | 6 | 1/4" | 4 | 6,4 | 15,0 | 400,0 | 1840 | 100 |
| **HW 208** | 8 | 5/16" | 5 | 7,9 | 16,6 | 400,0 | 1470 | 115 |
| **HW 210** | 10 | 3/8" | 6 | 9,5 | 19,0 | 400,0 | 1320 | 130 |
| **HW 213** | 12 | 1/2" | 8 | 12,7 | 22,2 | 400,0 | 1200 | 180 |

DN = Nominal diameter, nominal width

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*