


# KP 200 NO (2SC)

Compact hose

## Properties

<b>Application</b>	Medium pressure circuits with restricted installation spaces and extreme environmental conditions
<b>Standard</b>	EN 857 2 SC
<b>Inner layer</b>	oil resistant synthetic rubber
<b>Insert</b>	two high-tensile steel wire braids
<b>Outer layer</b>	synthetic rubber with high ozone, abrasion, and weather resistance
<b>Colour</b>	black
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	100 °C
<b>Elongation</b>	+ 2 % to - 4 %



## Note

The change in length of the hose is determined at max. working pressure during testing to EN ISO 1402.

## Item

Identification	DN*	Size	Inches	Internal Ø (mm)	External Ø (mm)	Operating pressure (bar)	Test pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)
KP 206 NO	6	4	1/4"	6,4	14,0	400,0	800	1600	75
KP 208 NO	8	5	5/16"	7,9	15,6	350,0	700	1400	85
KP 210 NO	10	6	3/8"	9,5	17,8	330,0	660	1320	90
KP 213 NO	12	8	1/2"	12,7	21,3	275,0	550	1100	130

DN = Nominal diameter, nominal width