


# KP 200 PRO (2SC)

HD hose, compact, abrasion resistant

**HANSA FLEX**

## Properties

<b>Application</b>	Medium pressure circuits with restricted installation spaces and high abrasion.
<b>Special features</b>	narrow bending radius extremely abrasion resistant top cover
<b>Standard</b>	EN 857 2 SC
<b>Inner layer</b>	oil resistant synthetic rubber
<b>Insert</b>	two high tensile steel wire braided inserts
<b>Outer layer</b>	synthetic rubber with additional plastic cover, with more than 300 x the abrasion properties of standard outer covers
<b>Colour</b>	black
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	100 °C
<b>Elongation</b>	+ 2 % to - 4 %
<b>Media</b>	Mineral oil Polyglycol based oil Water (0°C to + 70°C) Water-oil emulsions



## Note

The change in length of the hose is determined at max. working pressure during testing to EN ISO 1402.

## Item

Identification	DN*	Size	Inches	Internal Ø (mm)	External Ø (mm)	Operating pressure (bar)	Test pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)
KP 206 PRO	6	4	1/4"	6,4	13,7	400,0	800	1600	75
KP 208 PRO	8	5	5/16"	7,9	15,6	350,0	700	1400	85
KP 210 PRO	10	6	3/8"	9,5	17,8	330,0	660	1320	90
KP 213 PRO	12	8	1/2"	12,7	21,5	275,0	550	1100	130
KP 216 PRO	16	10	5/8"	15,9	25,1	250,0	500	1000	170
KP 220 PRO	19	12	3/4"	19,4	28,6	215,0	430	860	200
KP 225 PRO	25	16	1"	25,7	34,9	165,0	330	660	250

DN = Nominal diameter, nominal width