KUEHLER
Radiator hose

HANSA-FLEX

Properties



Application	Radiator hose
Standard	DIN 73411
Inner layer	EPDM
Insert	up to ID 19: one polyester braided insert; from ID 20: one Rayon braided insert
Outer layer	EPDM (from ID 20 mm patterned material)
Colour	black
Temp. min.	-40 °C
Temp. max.	120 °C
Media	Cooling water Cooling fluids

Item

Identification	ID x Wall thickness	Operating pressure (bar)	Burst pressure (bar)	Roll length (m)
KUEHLER 08-3.5	8 x 3.5	4,0	12	40
KUEHLER 10-3.5	10 x 3.5	4,0	12	40
KUEHLER 12-3.5	12 x 3.5	4,0	12	40
KUEHLER 13-3.5	13 x 3.5	4,0	12	40
KUEHLER 15-3.5	15 x 3.5	4,0	12	40
KUEHLER 16-3.5	16 x 3.5	4,0	12	40
KUEHLER 18-3.5	18 x 3.5	4,0	12	40
KUEHLER 20-3.5	20 x 3.5	4,0	12	40
KUEHLER 22-3.5	22 x 3.5	4,0	12	40
KUEHLER 25-3.5	25 x 3.5	4,0	12	40
KUEHLER 28-4	28 x 4	4,0	12	40
KUEHLER 30-4	30 x 4	4,0	12	40
KUEHLER 32-4	32 x 4	4,0	12	40
KUEHLER 35-4	35 x 4	4,0	12	40
KUEHLER 38-5	38 x 5	4,0	12	40
KUEHLER 40-5	40 x 5	4,0	12	40
KUEHLER 42-5	42 x 5	4,0	12	40
KUEHLER 45-5	45 x 5	4,0	12	40
KUEHLER 50-5	50 x 5	4,0	12	40
KUEHLER 55-5	55 x 5	4,0	12	40
KUEHLER 60-5	60 x 5	4,0	12	40
KUEHLER 70-5	70 x 5	4,0	12	40
KUEHLER 90-6	90 x 6	4,0	12	40

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.