

<b>Properties</b>				
Application	Radiator hose			
Standard	DIN 73411			
Inner layer	EPDM			
Insert	up to ID 19: one polyester braided insert; from ID 20: one Rayon braided insert			
Outer layer	EPDM (from ID 20 mm patterned material)			
Colour	black			
Temp. min.	-40 °C			
Temp. max.	120 °C			
Media	Cooling water Cooling fluids			



Item					
Identification	ID x Wall thickness	Operating pressure	Burst pressure	Roll length	
		(bar)	(bar)	(m)	
KUEHLER 08-3.5	8 x 3.5	4,0	12	40	
<b>KUEHLER 10-3.5</b>	10 x 3.5	4,0	12	40	
<b>KUEHLER 12-3.5</b>	12 x 3.5	4,0	12	40	
<b>KUEHLER 13-3.5</b>	13 x 3.5	4,0	12	40	
<b>KUEHLER 15-3.5</b>	15 x 3.5	4,0	12	40	
<b>KUEHLER 16-3.5</b>	16 x 3.5	4,0	12	40	
<b>KUEHLER 18-3.5</b>	18 x 3.5	4,0	12	40	
<b>KUEHLER 20-3.5</b>	20 x 3.5	4,0	12	40	
<b>KUEHLER 22-3.5</b>	22 x 3.5	4,0	12	40	
<b>KUEHLER 25-3.5</b>	25 x 3.5	4,0	12	40	
KUEHLER 28-4	28 x 4	4,0	12	40	
KUEHLER 30-4	30 x 4	4,0	12	40	
KUEHLER 32-4	32 x 4	4,0	12	40	
KUEHLER 35-4	35 x 4	4,0	12	40	
KUEHLER 38-5	38 x 5	4,0	12	40	
KUEHLER 40-5	40 x 5	4,0	12	40	
KUEHLER 42-5	42 x 5	4,0	12	40	
KUEHLER 45-5	45 x 5	4,0	12	40	
KUEHLER 50-5	50 x 5	4,0	12	40	
KUEHLER 55-5	55 x 5	4,0	12	40	
KUEHLER 60-5	60 x 5	4,0	12	40	
KUEHLER 70-5	70 x 5	4,0	12	40	
KUEHLER 90-6	90 x 6	4,0	12	40	