


# NY 2100

Thermoplastic extreme pressure hose

**HANSA FLEX**

## Properties

<b>Application</b>	Extreme pressure applications high pressure tools emergency rescue systems The jaws of life
<b>Special features</b>	Extremely kink-resistant hose good flexibility at low temperatures
<b>Inner layer</b>	Polyamide
<b>Insert</b>	one aramide braided insert and one high tensile steel wire braided insert
<b>Outer layer</b>	Polyurethane
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	100 °C
<b>Media</b>	Mineral oil Synthetic oils



## Item

Identification	DN*	Size	Inches	Internal Ø (mm)	External Ø (mm)	Operating pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)	Colour
<b>NY 2106</b>	6	4	1/4"	6,3	13,3	700,0	2800	70	black
<b>NY 2106 B</b>	6	4	1/4"	6,3	13,3	700,0	2800	70	blue
<b>NY 2106 GE</b>	6	4	1/4"	6,3	13,3	700,0	2800	70	yellow
<b>NY 2106 R</b>	6	4	1/4"	6,3	13,3	700,0	2800	70	red

DN = Nominal diameter, nominal width