


## Properties

<b>Application</b>	general application for air, water etc.
<b>Special features</b>	Hardness: approx. 77° Shore A environmentally and free of heavy metals abrasion and aging resistant sterilisable permanently transparent very flexible
<b>Inner layer</b>	Soft PVC
<b>Insert</b>	one braided textile insert
<b>Outer layer</b>	Soft PVC
<b>Colour</b>	green
<b>Temp. min.</b>	-5 °C
<b>Temp. max.</b>	60 °C
<b>Media</b>	Water Air



## Item

Identification	Internal Ø (mm)	External Ø (mm)	Wall thickness (mm)	BD* at 20 °C (bar)	Min. bending radius (mm)
PSG 06-3 GRUEN	6,0	12,0	3,0	23	25
PSG 08-3 GRUEN	8,0	14,0	3,0	22	30
PSG 10-3 GRUEN	10,0	16,0	3,0	17	40
PSG 13-3.5 GRUEN	13,0	20,0	3,5	13	60

BD = Working pressure

## Product versions

<b>PSG</b>	PVC hose with braided insert, clear
<b>PSG BLAU</b>	PVC hose with braided insert, blue
<b>PSG ROT</b>	PVC hose with braided insert, red
<b>PSG SCHWARZ</b>	PVC hose with braided insert, black