


Properties

| | |
|-------------------------|---|
| Application | general application for air, water etc. |
| Special features | Hardness: approx. 77° Shore A environmentally and free of heavy metals abrasion and aging resistant sterilisable permanently transparent very flexible |
| Inner layer | Soft PVC |
| Insert | one braided textile insert |
| Outer layer | Soft PVC |
| Colour | green |
| Temp. min. | -5 °C |
| Temp. max. | 60 °C |
| Media | Water Air |



Item

| Identification | Internal Ø (mm) | External Ø (mm) | Wall thickness (mm) | BD* at 20 °C (bar) | Min. bending radius (mm) |
|------------------|--------------------|--------------------|------------------------|-----------------------|-----------------------------|
| PSG 06-3 GRUEN | 6,0 | 12,0 | 3,0 | 23 | 25 |
| PSG 08-3 GRUEN | 8,0 | 14,0 | 3,0 | 22 | 30 |
| PSG 10-3 GRUEN | 10,0 | 16,0 | 3,0 | 17 | 40 |
| PSG 13-3.5 GRUEN | 13,0 | 20,0 | 3,5 | 13 | 60 |

BD = Working pressure

Product versions

| | |
|--------------------|-------------------------------------|
| PSG | PVC hose with braided insert, clear |
| PSG BLAU | PVC hose with braided insert, blue |
| PSG ROT | PVC hose with braided insert, red |
| PSG SCHWARZ | PVC hose with braided insert, black |