
PSG ROT

PVC hose with braided insert

Properties



Application	general application for air, water etc.
Special features	Hardness: approx. 77° Shore A environmentally and free of heavy metals abrasion and aging resistant sterilisable permanently transparent very flexible
Inner layer	Soft PVC
Insert	one braided textile insert
Outer layer	Soft PVC
Colour	red
Temp. min.	-5 °C
Temp. max.	60 °C
Media	Water Air

Item

Identification	Internal Ø (mm)	External Ø (mm)	Wall thickness (mm)	BD* at 20 °C (bar)	Min. bending radius (mm)
PSG 06-3 ROT	6,0	12,0	3,0	23	25
PSG 08-3 ROT	8,0	14,0	3,0	22	30
PSG 09-3 ROT	9,0	15,0	3,0	19	35
PSG 10-3 ROT	10,0	16,0	3,0	17	40
PSG 13-3.5 ROT	13,0	20,0	3,5	13	60
PSG 19-4 ROT	19,0	27,0	4,0	12	100

BD = Working pressure

Product versions

PSG	PVC hose with braided insert, clear
PSG BLAU	PVC hose with braided insert, blue
PSG GRUEN	PVC hose with braided insert, green
PSG SCHWARZ	PVC hose with braided insert, black

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.