


## Properties

<b>Application</b>	general application for air, water etc.
<b>Special features</b>	Hardness: approx. 77° Shore A environmentally and free of heavy metals abrasion and aging resistant sterilisable permanently transparent very flexible
<b>Inner layer</b>	Soft PVC
<b>Insert</b>	one braided textile insert
<b>Outer layer</b>	Soft PVC
<b>Colour</b>	black
<b>Temp. min.</b>	-5 °C
<b>Temp. max.</b>	60 °C
<b>Media</b>	Water Air



## Item

Identification	Internal Ø (mm)	External Ø (mm)	Wall thickness (mm)	BD* at 20°C (bar)	Min. bending radius (mm)
PSG 06-3 SCHWARZ	6,0	12,0	3,0	23,0	25
PSG 09-3 SCHWARZ	9,0	15,0	3,0	19,0	35
PSG 10-3 SCHWARZ	10,0	16,0	3,0	17,0	40
PSG 13-3.5 SCHWARZ	13,0	20,0	3,5	13,0	60

BD = Working pressure

## Product versions

<b>PSG</b>	PVC hose with braided insert, clear
<b>PSG BLAU</b>	PVC hose with braided insert, blue
<b>PSG GRUEN</b>	PVC hose with braided insert, green
<b>PSG ROT</b>	PVC hose with braided insert, red