

SI 200

Fuel hose with braiding

HANSA FLEX

Properties

Application Low pressure hose for fuel lines

Standard DIN 73379

Inner layer oil resistant synthetic rubber

Insert one braided textile insert


Outer layer none

Colour black

Temp. min. -35 °C

Temp. max. 80 °C

Media Petrol fuels
Diesel
Crude oil
Lubricating oil



Item

Identification	DN*	Inches	Size	Internal Ø (mm)	External Ø (mm)	Operating pressure (bar)	Test pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)
SI 202	2	3/32"	1	3,2	7,0	20,0	30	60	20
SI 203	3	1/8"	2	4,5	9,5	20,0	30	60	25
SI 204	4	3/16"	3	5,5	10,5	20,0	30	60	25
SI 206	6	1/4"	4	7,5	12,5	15,0	25	50	30
SI 208	8	5/16"	5	9,5	15,0	15,0	25	50	40
SI 210	10	3/8"	6	11,5	17,0	15,0	25	50	45
SI 213	12	1/2"	8	15,0	22,0	12,0	20	40	50
SI 216	16	5/8"	10	18,0	26,0	12,0	20	38	70

DN = Nominal diameter, nominal width