


SI 200

Fuel hose with braiding

HANSA FLEX

Properties

Application	Low pressure hose for fuel lines
Standard	DIN 73379
Inner layer	oil resistant synthetic rubber
Insert	one braided textile insert
Outer layer	none
Colour	black
Temp. min.	-35 °C
Temp. max.	80 °C
Media	Petrol fuels Diesel Crude oil Lubricating oil



Item

Identification	DN*	Inches	Size	Internal Ø (mm)	External Ø (mm)	Operating pressure (bar)	Test pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)
SI 202	2	3/32"	1	3,2	7,0	20,0	30	60	20
SI 203	3	1/8"	2	4,5	9,5	20,0	30	60	25
SI 204	4	3/16"	3	5,5	10,5	20,0	30	60	25
SI 206	6	1/4"	4	7,5	12,5	15,0	25	50	30
SI 208	8	5/16"	5	9,5	15,0	15,0	25	50	40
SI 210	10	3/8"	6	11,5	17,0	15,0	25	50	45
SI 213	12	1/2"	8	15,0	22,0	12,0	20	40	50
SI 216	16	5/8"	10	18,0	26,0	12,0	20	38	70

DN = Nominal diameter, nominal width