

# SI 200

Fuel hose with braiding

**HANSA FLEX**

## Properties

**Application** Low pressure hose for fuel lines

**Standard** DIN 73379

**Inner layer** oil resistant synthetic rubber

**Insert** one braided textile insert

**Outer layer** none

**Colour** black

**Temp. min.** -35 °C

**Temp. max.** 80 °C

**Media** Petrol fuels  
Diesel  
Crude oil  
Lubricating oil



## Item

Identification	DN*	Inches	Size	Internal Ø (mm)	External Ø (mm)	Operating pressure (bar)	Test pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)
SI 202	2	3/32"	1	3,2	7,0	20,0	30	60	20
SI 203	3	1/8"	2	4,5	9,5	20,0	30	60	25
SI 204	4	3/16"	3	5,5	10,5	20,0	30	60	25
SI 206	6	1/4"	4	7,5	12,5	15,0	25	50	30
SI 208	8	5/16"	5	9,5	15,0	15,0	25	50	40
SI 210	10	3/8"	6	11,5	17,0	15,0	25	50	45
SI 213	12	1/2"	8	15,0	22,0	12,0	20	40	50
SI 216	16	5/8"	10	18,0	26,0	12,0	20	38	70

DN = Nominal diameter, nominal width