

# PHD 100 VA

Swage ferrule for braided hose

## Properties

|                     |   |
|---------------------|---|
| <b>Ferrule type</b> | Skive ferrule / non-skive ferrule   |
| <b>suitable for</b> | Skive ferrule: 1SN (HD 100, HD 100T, HF 100, HW 100)<br>1SC (KP 100)<br>2SC (KP 200, KP 200PRO, KP 200S)<br>Non-skive ferrule: 1SN (HD 100), 1SC (DN 16, 19, 25)<br>2TE (TE 200B, DN06 to DN25) |
| <b>Material</b>     | Stainless steel   |



## Note

The ferrule assignment depends on the hose type.

## Item

| Identification | DN* | Size | Inches | D1<br>(mm) | D3<br>(mm) | LF<br>(mm) |
|----------------|-----|------|--------|------------|------------|------------|
| PHD 106 VA     | 6   | 4    | 1/4"   | 20         | 10,4       | 34,5       |
| PHD 108 VA     | 8   | 5    | 5/16"  | 22         | 12,0       | 34,5       |
| PHD 110 VA     | 10  | 6    | 3/8"   | 25         | 14,0       | 35,0       |
| PHD 113 VA     | 12  | 8    | 1/2"   | 28         | 17,3       | 37,0       |
| PHD 116 VA     | 16  | 10   | 5/8"   | 32         | 20,3       | 40,0       |
| PHD 120 VA     | 19  | 12   | 3/4"   | 36         | 24,3       | 45,0       |
| PHD 125 VA     | 25  | 16   | 1"     | 45         | 32,3       | 50,0       |
| PHD 132 VA     | 31  | 20   | 1.1/4" | 55         | 37,8       | 70,0       |
| PHD 140 VA     | 38  | 24   | 1.1/2" | 60         | 45,0       | 70,0       |
| PHD 150 VA     | 51  | 32   | 2"     | 76         | 57,5       | 80,0       |

DN = Nominal diameter, nominal width