PHY 300 Swage ferrule, NY 300

HANSA/FLEX

Properties	
Ferrule type	Non-skive ferrule
Material	Steel
Surface	electro galvanised
-	





Item

DN*	Size	Inches	D1	D3	LF	
			(mm)	(mm)	(mm)	
6	4	1/4"	18,0	11,3	43,0	
8	5	5/16"	20,0	11,3	40,0	
10	6	3/8"	23,0	13,7	47,0	
12	8	1/2"	29,0	16,6	50,0	
16	10	5/8"	32,0	19,9	60,0	
19	12	3/4"	37,0	24,5	60,0	
25	16	1"	42,0	29,5	60,0	
	6 8 10 12 16 19	6 4 8 5 10 6 12 8 16 10 19 12	6 4 1/4" 8 5 5/16" 10 6 3/8" 12 8 1/2" 16 10 5/8" 19 12 3/4"	6 4 1/4" 18,0 8 5 5/16" 20,0 10 6 3/8" 23,0 12 8 1/2" 29,0 16 10 5/8" 32,0 19 12 3/4" 37,0	(mm) (mm) 6 4 1/4" 18,0 11,3 8 5 5/16" 20,0 11,3 10 6 3/8" 23,0 13,7 12 8 1/2" 29,0 16,6 16 10 5/8" 32,0 19,9 19 12 3/4" 37,0 24,5	(mm) (mm) (mm) 6 4 1/4" 18,0 11,3 43,0 8 5 5/16" 20,0 11,3 40,0 10 6 3/8" 23,0 13,7 47,0 12 8 1/2" 29,0 16,6 50,0 16 10 5/8" 32,0 19,9 60,0 19 12 3/4" 37,0 24,5 60,0

DN = Nominal diameter, nominal width