

### Properties

|                    |   |
|--------------------|---|
| <b>Application</b> | Foundries, steelworks, glassworks, shipyards etc.                                   |
| <b>Application</b> | as contact protection for hot and cold hoses  |
| <b>Colour</b>      | smooth, rust red  |
| <b>Temp. min.</b>  | -65 °C  |
| <b>Temp. max.</b>  | 260 °C  |
| <b>Temp.</b>       | from inner diameter 6 mm to 127 mm: 1090 °C for 15-20 min. ; 1650 °C for 15-30 sec. |
| <b>Material</b>    | Calcium silicate fibres with a silicone cover                                       |



### Note

Permit from Germanischer Lloyd, DIN 5510-2; MSHA for internal diameter between 13 mm and 127 mm  
 Permit from Germanischer Lloyd for internal diameter above 160 mm  
 Above internal diameter 160 mm: Max. temperature: 300 °C

### Description

Provides outstanding protection against liquid metals and metal sprays.

### Additional information

good light, UV and weather proof, water and oil repellent effect.

### Item

| Identification | Internal Ø (mm) |
|----------------|-----------------|
| FBSB 006       | 6               |
| FBSB 008       | 8               |
| FBSB 010       | 10              |
| FBSB 013       | 13              |
| FBSB 016       | 16              |
| FBSB 019       | 19              |
| FBSB 022       | 22              |
| FBSB 025       | 25              |
| FBSB 029       | 29              |
| FBSB 032       | 32              |
| FBSB 035       | 35              |
| FBSB 038       | 38              |
| FBSB 041       | 41              |
| FBSB 044       | 44              |
| FBSB 051       | 51              |
| FBSB 057       | 57              |
| FBSB 064       | 64              |
| FBSB 070       | 70              |
| FBSB 076       | 76              |
| FBSB 083       | 83              |
| FBSB 089       | 89              |
| FBSB 095       | 95              |
| FBSB 102       | 102             |
| FBSB 114       | 114             |
| FBSB 127       | 127             |
| FBSB 160       | 160             |
| FBSB 170       | 170             |
| FBSB 180       | 180             |
| FBSB 200       | 200             |
| FBSB 220       | 220             |
| FBSB 250       | 250             |
| FBSB 300       | 300             |