

Properties

Application Foundries, steelworks, glassworks, shipyards etc.

Material Steel

Surface electro galvanised



Description

Zinc-plated steel wire protective braiding protects the hose against external damage such as flying sparks.

Item			
Identification	Internal Ø (mm)	External Ø (mm)	Min. bending radius (mm)
SGF 06	6	8,0	20
SGF 08	8	10,0	25
SGF 10	10	13,0	25
SGF 13	13	16,0	35
SGF 15	15	18,0	40
SGF 18	18	21,3	45
SGF 20	20	24,0	50
SGF 22	23	27,0	55
SGF 24	25	29,0	60
SGF 28	28	32,0	63
SGF 30	30	34,0	65
SGF 35	35	39,5	80
SGF 42	42	47,5	88
SGF 44	44	49,5	90
SGF 45	45	50,5	90
SGF 48	48	53,5	95
SGF 50	50	56,0	115
SGF 52	52	58,0	115
SGF 55	55	61,0	115
SGF 58	58	64,0	117
SGF 60	60	66,0	120
SGF 62	62	69,0	125
SGF 65	65	72,0	130
SGF 70	70	77,0	150
SGF 72	72	79,0	160
SGF 76	76	83,0	166
SGF 80	80	87,0	170