

**Properties**

<b>Application</b>	Foundries, steelworks, glassworks, shipyards etc.
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised

**Description**

Zinc-plated steel wire protective braiding protects the hose against external damage such as flying sparks.

**Item**

Identification	Internal Ø (mm)	External Ø (mm)	Min. bending radius (mm)
<b>SGF 06</b>	6	8,0	20
<b>SGF 08</b>	8	10,0	25
<b>SGF 10</b>	10	13,0	25
<b>SGF 13</b>	13	16,0	35
<b>SGF 15</b>	15	18,0	40
<b>SGF 18</b>	18	21,3	45
<b>SGF 20</b>	20	24,0	50
<b>SGF 22</b>	23	27,0	55
<b>SGF 24</b>	25	29,0	60
<b>SGF 28</b>	28	32,0	63
<b>SGF 30</b>	30	34,0	65
<b>SGF 35</b>	35	39,5	80
<b>SGF 42</b>	42	47,5	88
<b>SGF 44</b>	44	49,5	90
<b>SGF 45</b>	45	50,5	90
<b>SGF 48</b>	48	53,5	95
<b>SGF 50</b>	50	56,0	115
<b>SGF 52</b>	52	58,0	115
<b>SGF 55</b>	55	61,0	115
<b>SGF 58</b>	58	64,0	117
<b>SGF 60</b>	60	66,0	120
<b>SGF 62</b>	62	69,0	125
<b>SGF 65</b>	65	72,0	130
<b>SGF 70</b>	70	77,0	150
<b>SGF 72</b>	72	79,0	160
<b>SGF 76</b>	76	83,0	166
<b>SGF 80</b>	80	87,0	170