

### Properties

|                    |   |
|--------------------|---|
| <b>Application</b> | Hose lines that are subjected to a shearing load during movement. |
| <b>Colour</b>      | black   |
| <b>Temp. min.</b>  | -20 °C  |
| <b>Temp. max.</b>  | 60 °C   |
| <b>Material</b>    | Hard PVC  |



### Description

Flat plastic profile protective helix protects the hose against external abrasion.

### Additional information

Also suitable for retrofitting and for bundling hose lines.

### Item

| Identification | Internal Ø<br>(mm) | External Ø<br>(mm) | Wall thickness<br>(mm) |
|----------------|--------------------|--------------------|------------------------|
| SSK C 07       | 7,5                | -                  | -                      |
| SSK C 09       | 9,5                | -                  | -                      |
| SSK C 13       | 13,0               | 16,2               | 1,6                    |
| SSK C 16       | 16,0               | 19,5               | 1,7                    |
| SSK C 23       | 20,0               | 25,0               | 2,3                    |
| SSK C 30       | 27,0               | 32,2               | 2,6                    |
| SSK C 40       | 35,0               | 40,0               | 2,8                    |
| SSK C 50       | 43,5               | 49,5               | 3,0                    |
| SSK C 60       | 64,0               | 72,5               | 4,3                    |
| SSK C 80       | 81,0               | 91,0               | 5,0                    |