

Properties

| | |
|-------------|---|
| Application | Hose lines that are subjected to a shearing load during movement. |
| Colour | black |
| Temp. min. | -20 °C |
| Temp. max. | 60 °C |
| Material | Hard PVC |



Description

Flat plastic profile protective helix protects the hose against external abrasion.

Additional information

Also suitable for retrofitting and for bundling hose lines.

| Item | Identification | Internal Ø (mm) | External Ø (mm) | Wall thickness (mm) |
|----------|----------------|--------------------|--------------------|------------------------|
| SSK C 07 | SSK C 07 | 7,5 | - | - |
| SSK C 09 | SSK C 09 | 9,5 | - | - |
| SSK C 13 | SSK C 13 | 13,0 | 16,2 | 1,6 |
| SSK C 16 | SSK C 16 | 16,0 | 19,5 | 1,7 |
| SSK C 23 | SSK C 23 | 20,0 | 25,0 | 2,3 |
| SSK C 30 | SSK C 30 | 27,0 | 32,2 | 2,6 |
| SSK C 40 | SSK C 40 | 35,0 | 40,0 | 2,8 |
| SSK C 50 | SSK C 50 | 43,5 | 49,5 | 3,0 |
| SSK C 60 | SSK C 60 | 64,0 | 72,5 | 4,3 |
| SSK C 80 | SSK C 80 | 81,0 | 91,0 | 5,0 |